

# Product Data Sheet

**A79**



**Safety Products**



**Description:** Safety helmet with 4 point nylon web suspension with forehead comfort band, 4 point chin strap anchorage and 3-level height adjustment.  
The 30mm accessory slots fits most available accessories.



**Materials:** Shell – HDPE ( High Density Polyethylene ).  
Temp. resistance : -30 °C up to max +50°C  
Electrical properties : VDE-tested ( 1000 V).

**Total Weight:** 331 gram

**Standards:** EN397 – DIN VDE 0680

**Size :** 52 – 62 cm.

**Accessories :** Nomaz sweatband  
Penclip  
Faceshields  
Weldingshields  
Ear defenders  
Chinstraps (4-point).

Standards characteristics	EN 397
<b>Shock absorption</b>	
Form and mass	Spherical M = 5 Kg
Free fall and shock angle	H = 1 m vertical
<b>Maximum force</b>	<b>F maximum 5 kN</b>
<b>Resistance to penetration</b>	
Form and mass	 Conical (60° C) M = 3 Kg
Free fall and shock angle	H = 1 m vertical
Number of shocks	1 shock
<b>Requirement</b>	<b>No contact</b>
Flame resistance	Flame 10 s at 5 cm
Requirement	No burn more than 5 s
<b>Retention system strength</b>	
Released force	150 N < F < 250 N
Ventilation area	If ventilation 150 < S < 450 mm <sup>2</sup>

**End Shelf life:** Shell max. 5 years after first date of use.

**Storage :** Temp : min.+5°C and max. +25°C. Avoid direct sunlight.

**Packaging:** individual in polythene bag.  
20 helmets/Cse – LxWxH: 44.5x 31.8x 62.2cm – 08.02kg.

rev. 14-03-2006

North Safety Products  
The Netherlands  
Noordmonsterweg 1  
4332 SC Middelburg  
The Netherlands

Tel: +31(0)118 656400  
Fax: +31(0)118 627535

United Kingdom  
The Court Yard  
Green Lane, Heywood  
Lancashire OL10 2EX  
United Kingdom

Tel: +44(0)170 669 3800  
Fax: +44(0)170 669 3801

Germany  
Bramfelder Chaussee 41  
D-22177 Hamburg  
Germany

Tel: +49(0)40611775-0  
Fax: +49(0)40611775-10

France  
505 route de Bouc Bel Air  
13080 Luynes  
France

Tel: +33(0)442 240264  
Fax : +33(0)442 609530

Scandinavia  
Verktgsvägen 10  
S-55302 Jönköping  
Sweden

Tel: +46(0)36377241  
Fax: +46(0)36377629